Foerster resonance energy transfer in inhomogeneous non-dispersive nanophotonic environments

Wubs, Martijn; Vos, Willem L.

Publication date:
2016

Document Version
Publisher's PDF, also known as Version of record

Generation and Applications of High Average Power Mid-IR Supercontinuum in Chalcogenide Fibers

Christian Rosenberg Petersen*[1], Laurent Brilland[2], Johan Troles[3], Ole Bang[1,4]

[1] *DTU Fotonik, Department of Photonics Engineering, Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark,*
[2] *SelenOptics, 263 Avenue du Gal Leclerc, Campus de Beaulieu, 35700 Rennes, France.*
[3] *Equipe Verres et Céramiques, ISCR UMR-CNRS 6226, Université Rennes 1, 35042 Rennes Cedex, France.*
[4] *NKT Photonics A/S, Blokken 84, DK-3460 Birkerød, Denmark.*

**email: chru@fotonik.dtu.dk*

Abstract: Mid-infrared supercontinuum with up to 54.8 mW average power, and maximum bandwidth of 1.77-8.66 μm is demonstrated as a result of pumping tapered chalcogenide photonic crystal fibers with a MHz parametric source at 4 μm.

OCIS codes: (320.6629) Supercontinuum generation; (190.4370) Nonlinear optics, fibers; (060.2390) Fiber optics, infrared; (060.2290) Fiber materials; (160.4330) Nonlinear optical materials;